## (19) World Intellectual Property Organization International Bureau



# 

### (43) International Publication Date 28 September 2006 (28.09.2006)

## (10) International Publication Number WO 2006/100637 A2

(51) International Patent Classification: Not classified

(21) International Application Number: PCT/IB2006/050855

(22) International Filing Date: 20 March 2006 (20.03.2006)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 05102311.7

22 March 2005 (22.03.2005)

- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventor: and
- (75) Inventor/Applicant (for US only): DEANE, Steven, C. [GB/GB]; c/o Philips Intellectual Property, & Standards, Cross Oak Lane, Redhill Surrey RH1 5HA (GB).
- (74) Agents: WILLIAMSON, Paul, L. et al.; c/o Philips Intellectual Property, & Standards, Cross Oak Lane, Redhill Surrey RH1 5HA (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Declaration under Rule 4.17:


as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))

#### Published:

without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A SHIFT REGISTER CIRCUIT



- AA ... NOBUU . BB. ... RÉINITIALIS CC. ... T<sub>ATTAQUE</sub> . NœUD 1 . RÉINITIALISATION

(57) Abstract: Each stage of a shift register circuit has an input section (60) and an output section (62). The input section of each stage comprises an input section drive transistor (Tdrive) for coupling a first clocked power line voltage (Pn) to the output of the input section (60), an input section compensation capacitor (Ci) for compensating for the effects of a parasitic capacitance of the input section drive transistor (Tdrive) and a first input section bootstrap capacitor (C2) connected between the gate of the drive transistor and the output of the input section. The input section (60) of each stage uses the output (Rn-i) of the input section (60) of at least one preceding stage as a timing control input for controlling a bootstrap function, and the output section (62) of each stage comprises a circuit which receives the outputs of multiple input sections (60) as timing signals for generating output signals for the output loads (64). This circuit uses one stage to provide the required timing signals, and has feedback of timing signals between stages. This stage has low output load, and can therefore be realized with low size components, and the timing signal retain their shape even when there is degradation of the component characteristics. The other stage drives the load, and the output signals are not used as feedback timing signals, so that the output load does not degrade the timing control signals used in other stages.

